WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4:		11) International Publication Number: WO 8	6/ 02561
A61L 29/00	A1	43) International Publication Date: 9 May 1986	(09.05.86)
(21) International Application Number: PCT/SE (22) International Filing Date: 1 November 1985 (31) Priority Application Number: 8 (32) Priority Date: 2 November 1984 (33) Priority Country: (71)(72) Applicants and Inventors: BROHULT, Jo SE]; Bergenhielmsvägen 19A, S-161 53 Brom EDENROTH, Per [SE/SE]; Alvägen 7C, Sollentuna (SE). WERNER, Björn [SE/SE] desvägen 49, S-135 00 Saltsjöbaden (SE). (74) Agents: BURMAN, Tore et al.; Bergling & S. AB, Box 7645, S-103 94 Stockholm (SE).	(01.11.: 340550- (02.11.: han [S nma (S S-191; Vårg	ropean patent), CH (European patent), pean patent), FR (European patent), GB patent), IT (European patent), JP, LU (Eu tent), NL (European patent), SE (Eu	DE (Euro- (European ropean pa-
		EXIDINE AND A PROCESS FOR PRODUCING	

(54) Thie: PLASTIC OBJECT CONTAINING CHLORHEXIDINE AND A PROCESS FOR PRODUCING THE OBJECT

(57) Abstract

Plastic object intended for extended contact with living tissue, for example catheters, mainly consisting of a hydrophobic plastic, whereby it contains at least in connection with the surface chlorhexidine in a bactericidally effective amount; and process for the manufacture of such plastic objects using extrusion of a thermoplastic.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

٠,	AT	Austria	GA	Gabon .	MR	Mauritania
	AU	Australia	GB	United Kingdom	MW	Malawi
1	BB	Barbados	HU	Hungary	NL	Netherlands
1	BE	Belgium	IT	Italy	NO	Norway
1	BG	Bulgaria	JР	Japan	RO	Romania
1	BR	Brazil	KP	Democratic People's Republic	SD	Sudan
(CF	Central African Republic		of Korea	SE	Sweden
- (ĊG	Congo	KR	Republic of Korea	SN	Senegal
(CH	Switzerland .	LI	Liechtenstein	SU	Soviet Union
- (CM	Cameroon	LK	Sri Lanka	TD	Chad
1	DE	Germany, Federal Republic of	LU	Luxembourg	TG	Togo
1	DK	Denmark	MC	Monaco	US	United States of America
1	FI	Finland	MG	Madagascar.		
,	20	E	344	14-17		

§ 5

10

15

20

25

35

Plastic object containing chlorhexidine and a process for producing the object

The present invention relates to plastic objects which in practical use are in extended contact with living tissue. The invention also relates to a process for the manufacture of such plastic object. Plastic objects are known which are intended for implantation in the body or insertion in different parts of the body. Examples of such plastic objects are catheters, plastic prostheses of different types etc. One problem in using such plastic objects consists in the extended contact with surrounding tissue causing undesirable infections. Such problems arise for example nearly always in connection with urinarytract catheters resulting, in addition to the inconveniencies for the patient that the infection causes, that the catheter has to be replaced at relatively short intervals.

Different attempts to solve the problem have been made, mainly by trying to attach to the surface of the catheters anti-biotically or germicidally acting substances. However, hitherto no satisfactory solution to the problem has been found.

The present invention thus has for its object to provide a plastic object of the above-described type whereby the problem indicated is eliminated or at any rate substantially reduced. The invention also has for an object to provide a process for the manufacture of such plastic objects.

The present invention is based on the use of the bactericidally active substance chlorhexidine known per se the systematic chemical name of which is 1,1'-hexamethylenebis[5-(4-chlorophenyl)biguanide] having the following structural formula:

This substance of the trivial name chlorhexidine is an active antiseptic with bactericidal effect against gram-positive as well as gram-negative bacteria. In connection with the present invention it has now been surprisingly found that the substance chlorhexidine can be introduced in hydrofobic plastics so that these, at least in connection with the surface of the plastic object, contain the substance chlorhexidine. Thereby, the plastic

10

. 15

20

25

30

object in use causing extended contact with living tissue obtains a substantially reduced infection risk in that bacterial growth in connection with the plastic object is avoided or at any rate strongly inhibited. It is surprising that the bactericidal properties of the chlorhexidine are maintained in spite of the fixation in the hydrofobic plastic, and even if the invention is not limited to any specific theory concerning the mechanism of fixation it is conceivable that the chlorhexidine molecule is folded double in some manner so that the hydrofobic hydrocarbon chain in the middle is fixed in the plastic, whereas the bactericidally active terminal parts are externally accessible.

The chlorhexidine may be baked into the plastic mainly only in the surface layer of the plastic object but may alternatively be distributed across the whole mass of the plastic object.

In view of the process for the manufacture of the plastic objects according to the invention which will be described in detail below suitable plastics for the manufacture of the plastic objects are hydrofobic plastics of a thermoplastic nature. The character of the plastic or polymer in other respects is not chritical, since the chlorhexidine seems to be fixed by some sort of mechanical anchorage whereby the exact chemical composition of the plastic is not critical. Particularly preferred plastics or polymers are thermoplastic products prepared by a addition polymerisation from vinyl monomers, such as ethylene, vinyl chloride, styrene or propylene. Also other polyolefins are useful, for example polybutenes. Particularly preferred are polyethylene, polypropylene and polyvinyl chloride.

A bactericidally effective amount of the chlorhexidine is suitably at least about 0.1% by weight based on the part of the plastic material containing chlorhexidine. A preferred quantity range with regard to chlorhexidine is about 0.5 to about 1% by weight.

The invention provides, as previously indicated, also the process for the manufacture of the plastic object, and this process comprises xtrusion of a thermoplastic in a manner known per se, the thermoplastic in connection with the extrusion

```
but before cooling or self-cooling of the thermoolastic after leaving in solid form in the norther heins supplied with chlorhexidine
                                                but before cooling or self-cooling of the thermoplastic after leaving of the thermoplastic after leaving of the thermoplastic after leaving in solid form in the manufacture of plastic objects the north being supplied with manufacture of plastic objects the north being supplied the desired quantity.
                                                               the nozzle being supplied with manufacture of plastic distribute is substantially evenly distribute the desired quantity. For the is substantially evenly distribute the desired chlorhevidine is substantially evenly distribute.
                                                                         the desired quantity. For the manufacture of plastic objects is substantially evenly distributed is substantially evenly chlorhexidine is wherein whole mass of the plastic object the whole mass of the plastic object the chlorhexidine whole mass of the plastic object the chlorhexidine whole mass of the plastic object the chlorhexidine objects the chlorhexidine objects the chlorhexidine objects the chlorhexidine is the chlorhexidine of plastic objects the chlorhexidine is the chlorhexidine of plastic objects.
                                                                                            wherein the chlorhexidine plastic hefore feeding into the extrude in the whole mass of the plastic hefore feeding into the added to the themoniastic hefore feeding in the the thermoniastic hefore feeding in the the thermoniastic hefore feeding in the the thermoniastic hefore feeding in the thermoniastic hefore feedin
                                                                                                           in the whole mass of the plastic object the chlorhexidine is the whole thermoplastic before feeding orannines used before in the whole thermoplastic with the night or and to the thermoplastic with the night of the added to the thermoplastic with the night of the night of
                                                                                                                          added to the thermoplastic with the plastic granules used before and is suitably admixed with neare of feeding the extruder.
WO 86/02561
                                                                                                                                        and is suitably admixed with the plastic granules used be to the plastic granules used be supplied to the place of feeding can be supplied to the plastic granules used by the extruder.
                                                                                                                                                                                                                                                        arring same to the place of feeding the extruder.

the chlorhexidine arterial the connection with the arterial arrangement of the connection are also are also are also arrangement of the connection are also are al
                                                                                                                                                                 Alternatively, the chlorhexidine extrusion notile, and can be supplied to and can be supplied to and nainly the chlorhexidine is found mainly the chlorhexidine is found mainly the thermoplastic in procedure the chlorhexidine is found mainly the thermoplastic in procedure the chlorhexidine is found mainly the thermoplastic in procedure the chlorhexidine is found mainly the thermoplastic in procedure the chlorhexidine is found mainly the chlorhexidine in the chlorhexidine is found mainly the chlorhexidine is found mainly the chlorhexidine in the chlorhexidine is found the chlorhexidine in the chlorhexidine is found mainly the chlorhexidine in the chlorhexidine is found the chlorhexidine in the
                                                                                                                                                                               the thermoplastic in procedure the plastic object. This latter in this alternative layer of the only in the surface layer of the only in the surface layer of the old in this surface layer of the old in the old in the surface layer of the old in the old i
                                                                                                                                                                                                in this alternative procedure the chlorhexidine is found main in the surface of course. The result in a lesser consumption only in the does.
                                                                                                                                                                                                             only in the surface layer of the plastic of the plastic object will alternative does, of the other parts of the plastic object will alternative does, since the other parts of the plastic object will be surface to the other parts of the plastic object will be surface to the other parts of the plastic object will be surface the other parts of the plastic object will be surface the other parts of the plastic object will be surface the other parts of the plastic object will be surface the other parts of the plastic object will be surface the other parts of the plastic object will be surface the other parts of the plastic object will be surface the other parts of the plastic object.
                                                                                                                                                                                                                           alternative does, of the other parts of the plastic object will chlorhexidine, substance in question.
                                                                                                                                                                                                                                                                                                                                                        ntain the substance in question. wholly conventional and for example equity the manufacturing a placefic extender for example and the manufacturing a placefic extender.
                                                                                                                                                                                                                                                                     The manufacturing technique is wholly conventional and equipment technique is wholly conventional and example equipment that the manufacturing a plastic extruder, for example temporal a plastic extruder, for example a temporal ped with a feeding funnel, a feeder screw surrounded by a temporal ped with a feeding funnel, a feeder screw surrounded by a temporal ped with a feeding funnel, a feeder screw surrounded by a temporal ped with a feeding funnel, a feeder screw surrounded by a temporal ped with a feeding funnel, a feeder screw surrounded by a temporal ped with a feeding funnel, a feeder screw surrounded by a feede
                                                                                                                                                                                                                                                                              can be carried out using a plastic extruder, for example equip-
for example equip-
temps, for example ex
                                                                                                                                                                                                                                                                                             ped with a feeding mantle, heating means be supplied either to may thus be supplied either to the controlling mantle, heating thus the chlorhexidine in this case the chlorhexidine
                                                                                                                                                                                                                                            chlornexicane; substance in question.
                                                                                                                                                                                                                                                                                                                 erature controlling mantle, neating means and a suitable nozzle and a suitable nozzle, neating means and a suitable into may thus be supplied either to may thus be fore feeding into he chlorhexidine therein he fore feeding into the chlorhexidine and admixed therein he fore feeding into the nlastic material and admixed the nlastic material and 
                                                                                                                                                                                                                                                                                                                               In this case the chlorhexidine may thus be supplied exther to may thus be supplied in the the plastic material and admixed therein a later stage in the the feeding funnel or may be supplied at a later funnel or may be supplied at a later stage.
                                                                                                                                                                                                                                                                                                                                              the plastic material and admixed therein before feeding in the now the feeding funnel or may be supplied at a later with the now the feeding process.
                                                                                                                                                                                                                                                                                                                                                          the feeding funnel or may be supplied at a later with the nozz-

the feeding process, either before in pulverulent form.

extrusion process, chlorhexidine

extrusion process chlorhexidine
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           in pulverulent form. described in pulverulent form. described in pulverulent form. described in the following be described in the following be described in the plastics used in the present invention will examples. The plastic used in the present invention with non-limiting examples.
                                                                                                                                                                                                                                                                                                                                                                         extrusion process, elther before in pulverulent form.

chlorhexidine in the following he invention will in the following he in the following he invention will in the following he in the follo
                                                                                                                                                                                                                                                                                                                                                                                                        The present invention will in the rollowing be described in the ro
                                                                                                                                                                                  15
                                                                                                                                                                                                                                                                                                                                                                                                                     in connection with non-limiting examples. The plastics used if the and polyvinyl chloride of the area of the plastic object according these examples are polyethylene of the plastic object according these shown.
                                                                                                                                                                                                                                                                                                                                                                                                                                   these examples are polyethylene and polyvinyl chloride of the plastic object according the plastic object as used the plastic object as used the that the material used types shown is of such nature that the material types invention is of such plastic object.
                                                                                                                                                                                                                                                                                                                                                                                                                                                  types shown. The area of use of the plastic object according to the invention is of such mature that the material used to the invention of course to the invention of course to the should of course to the should of course to the should of course to the invention of the invention
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   of course, possess medicinal tolerability are manufactured tolerability of manufactured tolerability of catheters are manufactured tolerable test catheters are manufactured tolerable to the following examples test catheters are manufactured tolerable to the following examples test catheters are manufactured tolerable tolerab
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       In the following examples test catheters are manufactured, a feeding funnel, the following examples extruder having a feeding mantle for extrusion in a conventional temperature controlling mantle for by extrusion surrounded by a temperature controlling mantle for the following examples test catheters are manufactured in the following examples test catheters are controlling mantle for the following extruder controlling mantle for the following extrusion in the following examples test catheters are manufactured in the following examples the following examples the following examples the following examples to the following examples the following 
                                                                                                                                                                                                                                                                                                                                                                                                                                                                 To the invention is or such nature that the materia.

To the invention is possess medicinal tolerability.

To the invention is possess medicinal tolerability.
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        by extrusion in a conventional extruder the usual means in connection with a feeder screw surrounded by a the usual means in connection with a feeder screw medium and the usual means in connection with
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      a feeder screw surrounded by a temperature controlling mantle for the usual means in connection on the usual means is surrounded in only and the usual means is surrounded in only and the usual means is surrounded in only and the arterision portion the chiorheavisine is surrounded in only and the arterision portion the chiorheavisine is surrounded to the arterision portion the chiorheavisine is surrounded to the arterision portion to the chiorheavisine is surrounded to the chiorheavisine is surrounded to the usual means in connection on the chiorheavisine is surrounded to the usual means in connection of the chiorheavisine is surrounded to the usual means in connection of the usual means in connection of the usual means is surrounded to the usual means in connection of the usual means in connection of the usual means is surrounded to the usual means in connection of the usual means in connection of the usual means is surrounded to the usual means in connection of the usual means in the chiorheavision of the usual means in the usual means in the chiorheavision of the usual means in the usual 
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     a heat-transfer medium and the usual means is supplied in pulverus is supplied in the area the extrusion nozzle.

The chlorhexidine plastic material in the area the extrusion has spraying of the plastic material in the area the form either by spraying of the plastic material in the area the extrusion nozzle.
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 the extrusion nozzle. The chlorhexidine plastic material in the in the lent form either by spraying of the extrusion nozzle or by admixture in the lent immediately ahead of the extrusion nozzle or by almost alent immediately
                                                                                                                                                                                                                                                                                                                               25
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  lent form either by spraying of the plastic material in the area in the lent form either by serial used before feeding into the feeding funnel.
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              immediately anead of the extrusion nozzle or the feeding funnel.

plastic material used before feeding into
                                                                                                                                                                                                                                                                                                                                                                                                        30
                                                                                                                                                                                                                                                                                                                                                                                                    *
                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  35
```

WO 86/02561 PCT/SE85/00430

In the former case no exact knowledge will be obtained about the contents of chlorhexidine in the surface of the catheter prepared, whereas in this later case the content can be calculated starting from the quantity of chlorhexidine admixed with the plastic.

ŝ

EXAMPLE 1

5

10

In the present example there is used as a starting material for the manufacture of catheters a PVC-plastic obtained from Thevinyl AB, Sweden, which is stated to be of the type GFM, i.e. PVC of suspension type. This plastic is medicinally tolerable and accepted by FDA, USA. The chlorhexidine is supplied by spraying of powder into the extruder immediately before entering of the material into the extrusion nozzle.

For investigating the bactericidal properties of the catheters made tests were performed using a number of different test bacteria. The test strains were taken from positive urinary cultures showing significant growth. As nutrient media there were used nutrient broth (Bidife, Milano, Italy) prepared according to the instructions of the manufacturer and transferred in quantities of 5 mls in test tubes before sterilization. As a solid medium there was used test agar (PDM antibiotic sensitivity medium, AB Biodisk) prepared according to the instructions and transferred into 9 cms sterile petridishes.

For the manufacture of inoculate there was used (a) coli-25 form bacteria. Suspension of 5 colonies in 1 ml sterile 0.9% saline. While using a graded plastic loop 1/ul of suspension was transferred into 1 ml of saline.

- (b) staphylococci, enterococci, streptococci Group B. 5 colonies are suspended in 5 mls 0.9% saline;
- 30 (c) beta- and alphastreptocci. 10 colonies are suspended in 1 ml 0.9% saline.

A tube containing 5 mls of broth was inoculated with one drop (0.025 ml) of bacterial suspension. A 4 cm piece of the catheter is placed in tubes and incubation is performed over night at 37°C. The growth is visually controlled. Each series consists of treated catheters and controls with untreated catheters and only inoculated tubes.

The results of the experiments as carried out are shown in following Table 1. In all cases growth of the test strain was observed both in tubes with treated catheters and with untreated catheters.

5 TABLE 1

25

35

	Bacterial strain	Number of tests	Number show- ing growth	. No growth
	Esh. coli	31	0	31
10	Klebsiella spp	13	10	3
	Proteus mirabilis	15	5	10
	Proteus vulgaris	2	2	0
	Ps auriginosa	12	4	8
	Enterococcus	13	3	10
15	Staph.saprophyticus	5	0	5
	Staph.aureus	8 .	0	8
	Staph.epidermidis	18	6	12
	β -strep. group B	8	0 .	8

As is clear from the table in the majority of cases no growth of the respective bacterial strains was obtained.

EXAMPLE 2

Catheters were made from the same plastic material as in Example 1 but this time while adding the chlorhexidine in the starting material by admixing therein before transfer to the feeder funnel. The following quantities chlorhexidine were added:

	Test	catheter	A1	0.5 g	chlorhexidine	per	kg c	of plastic
	11	11	A2	1.0 g	17	**	**	**
	11	11	A3	2.0 g	. 11	**	**	**
30	17	17	A4	5.0 g	11	**	**	**
	**	Ħ	A 5	10.0 σ	11	11	11	11

All catheters were tested against 22 different strains of E.coli, the growth being made submersive to ensure that the test strain grew and not a contaminant. The results of these tests are presented in Table 2.

TABLE 2

		•	Cathet	er		
	Strain	A1	A2	A3	A4	A5
e	E. coli 6.	· •	+	•	0	o .
5	7	+ .	+	+	+	0
	8	•	+	0	0	0
	9	+	0	0	0	0
10	10	+ .	+	+	o	0
	11	+	+	+	+	0
	12	+	•	+	•	0
	. 13	+	. 0 .	0	0	. 0
15	14	•	0	0	O	0
	. 15	+	+	+	. 0	0
	. 16	.· + ·	. +	.	0	٠.
20	17	•	+ ·	+ ,	+	0
20	18	+	0		•	0
	19	+	+	+	0	• 0
	20	+	+	+		o
25	. 21	+	+ .	. •	0	o.
	22	•	0	•	0	0
	23	+	0	. +	+	0
	24	+	. +	+	. 0	0
30	25	+	+	+	0	o G
	26	+	+	+		0
	27	+	+	• •	. 0	J

35

Note + = growth of test strain

n = no growth

The table speaks its clear language and shows that a quantity of chlorhexidine of about 0.05% does not give any effect on growth, whereas at increasing concentration the chlorhexidine inhibition of the growth increases. Even if in many cases a concentration of 0.2% of chlorhexidine gives an effect it is clear from the table that it is preferred to use a quantity of hexidine of at least about 0.5% by weight, whereas for economical reasons it does not seem to be necessary to increase the concentration over about 1% by weight.

10 EXAMPLE 3

5

15

Catheters were manufactured in accordance with the technique according to Example 2 but instead of polyvinylchloride there was used a highmolecular polyethylene of low density of the type Lupolen 1810D from BASF, DDR. Experiments were carried out with 12 different E.coli-strains while adding chlorhexidine to the plastic starting material in a quantity of 2 and 5 gs per kg, respectively. The results of the experiments are shown in Table 3.

TABLE 3

20			Po	lyethylened	catheter
	Bacterial	strain	2	gs/kg !	5 gs/kg
	E.coli 1		+	•	-
	2		+	•	-
	3		+	•	-
25	4		+	•	-
	5		+	(+	+)
	·6		+	•	•
	7		+	•	•
	8		+	-	-
30	9		(+)	•	-
	10		+	-	•
	11	·	+	-	•
	12		-	•	-
	Note.	+=growth	and -= n	o growth	

35

5

10

Further experiments have been made which verify the fact that autoclaving or washing of the plastic catheters containing chlorhexidine does not have any significant effect with regard to the bactericidal activity. Thus, the chlorhexidine is strongly anchored in the plastic, whereby the bactericidal effect can be maintained for a long period of time. In using the plastic objects according to the present invention thus for example catheters made in accordance with the invention can be left in position for longer periods of time without non-desirable infections arising.

CLAIMS

- 1. A plastic object intended for extended contact with living tissue, for example catheters, mainly consisting of a hydrophobic plastic, characterized thereby that it at least in connection with the surface contains chlorhexidine in a bactericidally effective amount.
- 2. A plastic object according to claim 1, characterized thereby that the chlorhexidine is baked into the plastic at least in the surface layer of the plastic object.
- 3. A plastic object according to claim 1 or 2, characterized thereby that the chlorhexidine is distributed in the whole plastic object.
- 4. A plastic object according to any preceding claim, characterized thereby that the hydrophobic plastic is polyvinylchloride.
- 5. A plastic object according to any of the claims 1-3, characterized thereby that the hydrophobic plastic is a polyolefin , for example polyethylene or polypropylene.
- 6. A plastic object according to any preceding claim, characterized thereby that the chlorhexidine is present in an amount of at least about 0.1% by weight based upon the part of the plastic containing same.
- 7. A plastic object according to claims 3 and 6, characterized thereby that the chlorhexidine is present in an amount within the range about 0.5 about 1% by weight.
- 8. A process for the manufacture of a plastic object according to claim 1, containing extrusion of a thermoplastic in a manner known per se, characterized thereby that the thermoplastic in connection with the extrusion and before the cooling or self-cooling of the thermoplastic after leaving the nozzle is supplied with chlorhexidine in solid form in the desired quantity.
- 9. A process according to claim 8, characterized thereby that the chlorhexidine is added to the thermoplastic before feeding into the extruder thereby being distributed mainly evenly in the plastic object.

10. A process according to claim 8, characterized thereby that the chlorhexidine is added to the thermoplastic in connection with the nozzle, whereby it is found mainly only in the surface layer of the plastic object.

INTERNATIONAL SEARCH REPORT

PCT/SE8500430 |

				international Application No	C1/3E0700430
I. CLASS	SIFICATI	ON OF	SUBJECT MATTER (if several class	ification symbols apply, indicate all) *	
			etent Classification (IPC) or to both Na	tional Classification and IPC 4	
A 61	L 2	9/00		•	
II. FIELD:	S SEARC	HED			
			Minimum Docume	ntation Searched 7	
lassificati	on System	!		Classification Symbols	
IPC	4	A	61 L 15/03, 29/00	; A 61 K 31/03;	
	_		01 N 25/08, /10		-
US C	:1	1 6	<u>04:265; 128:349; 4</u>		
			Documentation Searched other to the Extent that such Documents	than Minimum Documentation are included in the Fields Searched *	
	·				
		S	E, NO, DK, FI clas	ses as above	
III. DOCU	MENTS	CONSI	DERED TO BE RELEVANT		
ategory *	Cita	tion of I	Document, 11 with indication, where app	propriate, of the relevant passages 12	Relevant to Claim No. 13
]					
Y	EP,	Al,	0 022 289 (THE PROCOMPANY)	OTECTOR & GAMBLE	1-7
!		_	14 January 1981		.
į		£.	JP, 56045954 US, 4343798		
ļ			CA, 1156932		
!			US, 4479795		
:					
Y	DE,	A,	1 111 780 (AMERICA 27 July 1961	AN CYANAMID	1-7
Y	GB,	Α,	2 084 466 (RONALD	McNALLY)	1-7
; ; ;		&	15 April 1982 EP, 0050438 JP, 57090052	,	
!			,		
:					
į					
į	•				
1					
"A" docu	ument defi sidered to	ning the	d documents: 10 general state of the art which is not inticular relevance	"T" later document published after the or priority date and not in conflicted to understand the principle invention.	ct with the application but
filh	date		ublished on or after the international	"X" document of particular relevant cannot be considered novel or	e; the claimed invention cannot be considered to
Mylc	h is cited	to estai	throw doubts on priority claim(s) or blish the publication date of another	involve an inventive step "Y" document of particular relevance	e; the claimed invention
"O" docu	ıment refe		al reason (as specified) an oral disclosure, use, exhibition or	document is combined with one	or more other such docu-
othe	(Means		rior to the international fliing date but	ments, such combination being of in the art.	bylous to a person skilled
			tate claimed	"4" document member of the same p	atent family
	FICATIO				
ate of the	Actual Co	ompietic	n of the International Search	Date of Mailing of this International Sec	
1004	-01-1	0		1986 -01	- 15
T 200.				Claration of Authority 1 000	
1986-	al Searchin	ng Autho	onty	Signature of Authorized Offices . Trype - Lane	- Return